



HQC GLOSS

1. PRODUCT AND COMPANY IDENTIFICATION

| | |
|-----------------------------|--|
| 1.01 Product Code: | HQGL |
| 1.02 Product Name: | HQC Gloss |
| 1.03 Synonyms: | Thermilate Gloss Coating |
| 1.04 Manufacturer/Supplier: | Thermilate Technologies Ltd. |
| 1.05 Address: | Unit 48 Birds Royd Lane BRIGHOUSE West Yorkshire HD6 1NG |
| 1.06 Contact: | Operations Director |
| 1.07 Phone Number: | 0845 680 6124 |

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a physico-chemical, health or environmental hazard within the meaning of the CHIP Regulations or which are assigned occupational exposure limits.

| EC No. | CAS No. | HAZARDOUS INGREDIENTS | % | CLASSIFICATION |
|---|------------|---|-------------|---------------------------|
| FOR BLACK, WHITE AND PURE BRILLIANT WHITE: | | | | |
| 265-150-3 | 64742-48-9 | NAPHTHA (PETROLEUM), HYDROTREATED HEAVY | 10-25 Xn | R10-65-66-67 |
| 265-150-3 | 64742-48-9 | NAPHTHA (PETROLEUM), HYDROTREATED HEAVY | 2.5-10 Xn | R65-66 |
| 271-376-3 | 68551-41-7 | CALCIUM CARBOXYLATE | 1.0-2.5 Xi | R36/38 |
| 265-185-4 | 64742-82-1 | NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY | < 1.0 N, Xn | R10-51/53-65-66-67 |
| 202-496-6 | 96-29-7 | ETHYL METHYL KETOXIME | < 1.0 Xn | R21-40-41-43 Carc. Cat. 3 |
| FOR ALL OTHER COLOURS: | | | | |
| 265-150-3 | 64742-48-9 | NAPHTHA (PETROLEUM), HYDROTREATED HEAVY | 10-25 Xn | R10-65-66-67 |
| 265-150-3 | 64742-48-9 | NAPHTHA (PETROLEUM), HYDROTREATED HEAVY | 2.5-10 Xn | R65-66 |
| 271-376-3 | 68551-41-7 | CALCIUM CARBOXYLATE | 1.0-2.5 Xi | R36/38 |
| 265-185-4 | 64742-82-1 | NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY | < 1.0 N, Xn | R10-51/53-65-66-67 |
| 202-496-6 | 96-29-7 | ETHYL METHYL KETOXIME | < 1.0 Xn | R21-40-41-43 Carc. Cat. 3 |
| | | COBALT CARBOXYLATE | < 1.0 N, Xn | R22-38-43-51/53 |

Note: The text for R phrase codes shown above (if any) is given in section 16.

Note: 'EC Number' if quoted is the EINECS or ELINCS number.



HQC GLOSS

3. HAZARD INFORMATION

| | |
|-------------------------------|------|
| 3.01 Indication(s) of Danger: | None |
| 3.02 Symbol Letter(s): | None |
| 3.03 Category(ies) of Danger: | None |
| 3.04 Warning Label Phrases: | None |

FOR BLACK, WHITE AND PURE BRILLIANT WHITE: Contains ETHYL METHYL KETOXIME. May produce an allergic reaction.

FOR ALL OTHER COLOURS: Contains COBALT CARBOXYLATE, ETHYL METHYL KETOXIME. May produce an allergic reaction.

4. FIRST AID MEASURES

| | |
|--------------------|--|
| 4.01 Eye Contact: | Flush out with clean water for 10 minutes. Get medical help, if necessary. |
| 4.02 Skin Contact: | Wash area of contact with soap and water. |
| 4.03 Ingestion: | Seek urgent medical attention. DO NOT INDUCE VOMITING. |
| 4.04 Inhalation: | Move to fresh air, if unconscious turn into recovery position. Get medical help. |

5. FIRE PREVENTION MEASURES

| | |
|----------------------|--|
| 5.01 Small Fires: | Use Carbon Dioxide, dry chemical, foam, sand, earth or water fog. |
| 5.02 Large Fires: | Use foam or water fog. Keep containers cool by spraying with water. |
| 5.03 Not to be used: | Waterjet |
| N.B. | Decomposition products will give rise to toxic fumes. Self-contained breathing apparatus must be worn. |

6. ACCIDENTAL RELEASE MEASURES

Exclude non-essential personnel. Exclude sources of ignition and ventilate the area. Avoid breathing vapours. Contain and collect spillage with non-combustible absorbent materials, eg sand, earth, vermiculite or diatomaceous earth, and place in container for disposal according to local regulations. Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product enters drains or sewers, immediately contact the local water company; in the case of contamination of streams, rivers or lakes, the relevant environment agency.

7. HANDLING & STORAGE

7.01 HANDLING CONDITIONS:

Prevent air-borne concentrations higher than the occupational exposure limits. Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Avoid skin and eye contact. Avoid inhalation of vapour. Smoking, eating and drinking should be prohibited in storage and use areas. For personal protection, see Section 8. Always keep in containers made of the same material as the supply container, or in containers that are compatible with the product.

7.02 STORAGE CONDITIONS:

Observe the label precautions. Store in a cool, dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. Do not use or store any paint container by hanging on a hook.

The Manual Handling Operations Regulations 1993 may apply to the handling of certain Paint Products. Products packed in containers of 5 litres and above will be marked with a guide weight; refer to these weights when carrying out an assessment.

HQC GLOSS

7. HANDLING & STORAGE (CONTINUED)

The principles contained in the HSE guidance note Storage of Packaged Dangerous Substances, should be observed when storing this product. Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohols and water.

7.03 SPECIFIC USE(s):

Where applicable refer to the product label and literature for the application and use instructions.

8. PERSONAL PROTECTION MEASURES

EXPOSURE LIMIT VALUES

| HAZARDOUS INGREDIENT | LTEL (8hr TWA) ppm | LTEL (8hr TWA) mg/m ³ | STEL (15 mins) ppm | STEL (15 mins) mg/m ³ | Notes |
|-----------------------------------|--------------------|----------------------------------|--------------------|----------------------------------|-------|
| NAPHTHA (PETROLEUM), HYDROTREATED | | 1000 | | | OEL |
| NAPHTHA (PETROLEUM), HYDROTREATED | | 1000 | | | OEL |
| HYDRODESULFURIZED HEAVY | | 600 | | | OEL |
| ETHYL METHYL KETOXIME | 3 | 10 | | | SUP |
| NAPHTHA (PETROLEUM) | | 0.1 | | | WEL |

OEL - Occupational Exposure Limits

WEL -Workplace Exposure Limit

SUP -Manufacturer's recommended Limit

LTEL - Long-term Exposure Limit.

TWA - Time weighted Average

STEL - Short term Exposure Limit (15mins)

sk - Risk of absorption through unbroken skin

sen - Respiratory sensitiser

rd - Figure quoted is for Respirable dust

id - Figure quoted is for Inhalable dust

Further guidance on WELs and OELs, and on occupational exposure to harmful materials (including mixed exposures) is given in HSE Guidance Note EH40.

8.01 EXPOSURE CONTROLS:

Before commencing work, ensure that a COSHH Assessment has been carried out. All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of local regulations.

8.02 RESPIRATORY PROTECTION:

Avoid the inhalation of vapour, particulates and spray mist. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general ventilation. If this is not sufficient to maintain concentrations of particulates and solvent vapour below the occupational exposure limit, respiratory protection must be worn.

The selection of respiratory equipment should be in accordance with BS 4275. Recommendations for the selection, use and maintenance of Respiratory Equipment, and the current certificates of approval are issued annually by the Health and Safety Executive.

8.03 HAND PROTECTION:

Wear suitable gloves for protection against materials in section



HQC GLOSS

8. PERSONAL PROTECTION MEASURES (CONTINUED)

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed.

8.04 EYE PROTECTION:

Eye protection designed to protect against liquid splashes should be worn.

8.05 SKIN PROTECTION:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

8.06 FLATTING:

Protective gloves should be worn to avoid the risk of skin irritation. When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.

Where possible wet flattening or chemical stripping methods should be used with surfaces of this type to avoid the creation of dust. When dry flattening cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the occupational hygiene (COSHH) assessment, taking into account the occupational hygiene exposure standard for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

The Control of Lead at Work approved code of practice 1998 (ISBN 0 71 7615065) should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting contractor as Special (Hazardous) Waste, with the relevant documentation under The Special Waste Regulations 1996 plus amendment 2001, The Environmental Protection (Duty of Care) Regulations 1991, The Controlled Waste Registration of Carriers and Seizure of Vehicles Regulations 1991 plus amendment 1998 and the Controlled Waste Regulations 1992 plus amendment 1993.

8. PERSONAL PROTECTION MEASURES (CONTINUED)

Dry sanding, flame cutting and/or welding of the dry paint film may give rise to dust and/or hazardous fumes. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Extra precautions will need to be taken when burning off old lead based paints (See above - "Flattening" for relevance to work on older property, ie pre 1960) as fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the occupational hygiene (COSHH) assessment, taking into account the occupational hygiene exposure standard for lead in air. Similar precautions to those given above under the Flattening section should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.



HQC GLOSS

9. PHYSICAL DATA

| | |
|-----------------------------------|---|
| 9.01 Physical State: | Liquid |
| 9.02 Flash Point: | None |
| 9.03 Specific Gravity: | 0.9 - 1.2 |
| 9.04 Water Miscibility: | No |
| 9.05 pH: | No Information |
| 9.06 Viscosity: | > 100 (ISO 6mm Range) |
| 9.07 Initial Boiling Point in °C: | 150 |
| 9.08 Explosion limits: | Lower - approx. 0.8% Upper - no information |

10. STABILITY AND REACTIVITY

| | |
|---|---|
| 10.01 Conditions to avoid: | Extremes of temperature. |
| 10.02 Materials to avoid: | Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions. |
| 10.03 Hazardous decomposition products: | When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke and oxides of nitrogen. |

11. TOXICOLOGICAL DATA

There is no data available on the product itself. The product has been assessed following the conventional method in the CHIP Regulations and is classified for toxicological hazards accordingly. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact. See Sections 2 and 15 for details of the resulting hazard classification.

Over-exposures of vapour are irritating to eyes and respiratory system. Excessive concentrations may produce effects on the central nervous system including drowsiness. In extreme cases loss of consciousness may result. Long term exposure to vapour concentrations in excess of quoted OELs may result in adverse health effects. Splashes entering the eye will cause discomfort and possible damage. Prolonged contact with the skin may have a defatting effect which may lead to skin irritation and in some cases dermatitis.

This product contains methyl ethyl ketoxime. The classification given in Section 3 is in concurrence with Annex 1 of EU Directive 67/548/EEC. Ingestion studies in animals have shown that repeated doses have an adverse effect on the blood. A lifetime inhalation study in rats and mice produced damage to the nasal membranes and liver tumours. The relevance of the carcinogenicity findings to humans is uncertain. The new data may lead to a future reclassification of methyl ethyl ketoxime. Further studies are to be conducted.

12. ECOLOGICAL DATA

There is no specific data available on the product itself.

The product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

Products classified as Marine Pollutants are indicated as such under Transport (section 14).

Products classified as Dangerous For the Environment are indicated as such in sections 2 and 15.

Any substances in the product that are classified as Dangerous for the Environment, present at concentrations above those requiring listing are given in section 2.



HQC GLOSS

13. DISPOSAL

Wastes, including emptied containers, should be disposed of in accordance with national regulations.

CODES ACCORDING TO THE LIST OF WASTES REGULATIONS:

Product as supplied: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11.

Part-used containers, containing dried residues of the supplied product: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11

Used containers, rigorously scraped out and containing dried residues of the supplied product: Assigned as non-hazardous waste code 15 01 02 plastic packaging OR non-hazardous waste code 15 01 04 metal packaging.

“Rigorously scraped out” means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means.

These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.

14. TRANSPORT INFORMATION

| | |
|----------------------------------|------------|
| 14.01 UN number: | 1263 |
| 14.02 Proper Shipping Name: | PAINT |
| 14.03 Hazard Class: | 3 |
| 14.04 Sub-Hazard Class: | N/A |
| 14.05 Packing Group: | III |
| 14.06 Technical Name (NOS only): | N/A |
| 14.07 Ltd QtyMaximum: | 5.0 Litres |
| 14.07 Packing Instructions: | P001 |
| 14.07 Marine Pollutant: | None |
| 14.07 Emergency Schedule No: | F-E, S-E |
| 14.07 Flashpoint: | None |
| 14.08 Ltd Qty Code: | LQ7 |

In pack sizes up to and including 30 litres, under the terms of 2.3.2.5, this product is not subject to the packaging, labelling and marking requirements of the IMDG Code, but both full documentation and placarding of cargo transport units is still required. In pack sizes less than 450 litres, under the terms of 2.2.3.1.5, this product is not subject to the provisions of ADR.

15. REGULATORY INFORMATION

15.01 NAMED SUBSTANCES:

Contains No substances are required to be named in this section.

15.02 INDICATION(S) OF DANGER:

None

15.03 SYMBOLS LETTER(S):

None

15.04 WARNING LABEL PHRASES:

FOR BLACK, WHITE AND BRILLIANT WHITE:



TRADE - CLEAR

15. REGULATORY INFORMATION (CONTINUED)

| | |
|--------|---|
| S51 | Contains: ETHYL METHYL KETOXIME. May produce an allergic reaction. |
| J105 | When applying by brush or roller to large interior surface areas or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment. |
| S24/25 | Avoid contact with skin and eyes. |
| J33 | When applying it is advisable to wear eye protection. |
| S26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| S2 | Keep out of the reach of children. |
| S46 | If swallowed, seek medical advice immediately and show this container or label. |
| J15 | Do not use or store by hanging on a hook. |
| J82 | Do not empty into drains or watercourses. |
| J18 | Before use refer to the safety data sheet. |
| J110 | This includes waste hazard categories. |
| J50 | Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. |
| J44 | Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. |
| J47 | For further advice contact ICI Paints. |

FOR ALL OTHER COLOURS:

| | |
|------|---|
| P99 | Contains: ETHYL METHYL KETOXIME, COBALT CARBOXYLATE. May produce an allergic reaction. |
| J105 | When applying by brush or roller to large interior surface areas or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment. |

HQC GLOSS

15. REGULATORY INFORMATION (CONTINUED)

| | |
|--------|--|
| S24/25 | Avoid contact with skin and eyes. |
| J33 | When applying it is advisable to wear eye protection. |
| S26 | In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. |
| S2 | Keep out of the reach of children. |
| S46 | If swallowed, seek medical advice immediately and show this container or label. |
| J15 | Do not use or store by hanging on a hook. |
| J82 | Do not empty into drains or watercourses. |
| J18 | Before use refer to the safety data sheet. |
| J110 | This includes waste hazard categories. |
| J50 | Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. |
| J44 | Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. |
| J47 | J47 For further advice contact ICI Paints. |

Where 'J' and/or 'P' phrases are denoted, these are ICI Paints or paint industry reference codes to additional phrases. Label phrase according to the Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations:

EU limit value for this product (cat. A/d): 400 g/l (2007)/ 300 g/l (2010).
This product contains max. 300 g/l VOC.

16. OTHER INFORMATION

Text for R Phrases shown in section 3 describing each ingredient:

| | |
|--------|---|
| R22 | Harmful if swallowed. |
| R36/38 | Irritating to eyes and skin. |
| R38 | Irritating to skin. |
| R40 | Limited evidence of a carcinogenic effect. |
| R41 | Risk of serious damage to eyes. |
| R43 | May cause sensitisation by skin contact. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R65 | Harmful: may cause lung damage if swallowed. |
| R66 | Repeated exposure may cause skin dryness or cracking. |

This information should be used as a supplement to other information obtained to make independent judgement of suitability and to ensure proper use and protect the health and safety of employees.

Judgement as to the suitability of the information herein for the purchaser's purposes are necessarily purchaser's responsibility. Therefore although reasonable care has been taken in the preparation of such information, Thermilate Technologies Ltd extends no warranties, makes no representations and assumes no responsibility as to the accuracy of suitability of such information for application to purchasers intended purpose or for consequences of its use.

Prepared by Thermilate Technologies Ltd

Dated: 8th MAR 2013

Revised: HQGL.2.13

Reviewed: 10th OCT 2013

This Product Data Sheet supersedes all other previously dated sheets for this product.



SHEET

**HQGL
8.13**